STAINLESS STEEL SOLENOID VALVES

10-32 TO 2" NPT NORMALLY CLOSED & NORMALLY OPEN

2- & 3-WAY DIRECT ACTING









C9 & C4 Bar Stock bodies 10-32 to 3/8" NPT 303 Stainless Steel

C9 & C4 Cast bodies 1/8", 1/4", 3/8" NPT 316 Stainless Steel

S30 & S31 1/8", 1/4", 3/8" NPT 303 Stainless Steel

2-WAY PILOTED PISTON

2-WAY MINI-DIAPHRAGM







C9 & C4 Bar Stock bodies 10-32 to 3/8" NPT 303 Stainless Steel

C9 & C4 Cast bodies 1/8", 1/4", 3/8" NPT 316 Stainless Steel





Hot Water & Steam

10-32 TO 2" NPT NORMALLY CLOSED & NORMALLY OPEN

2-WAY PILOTED DIAPHRAGM







S21 3/8" to 2" 316 Stainless Steel 1 to 250 psi Water

2-WAY ZERO PRESSURE DIFFERENTIAL PILOTED DIAPHRAGM







S20 3/8" to 1-1/2" 316 Stainless Steel 0 to 140 psi Water S27 1" to 2" 316 Stainless Steel 0 to 100 psi Water

Other 2- & 3-way Designs:

- Bodies Stainless Steel, Brass, Polypropylene, Celcon, Nylon, Noryl, others
- Seals Nitrile, Viton, EPR, Teflon, Rulon, FFKM, Santoprene, others
- Electrical All Common AC & DC Voltages
- Housings Conduit, DIN, NEMA 7/9 Explosion Proof, Junction Box, Open Frame Leads
- Manifolds wide variety of standard products; designed to meet custom applications
- Approvals UL, CSA, CE, NSF



