




# TRUE UNION SOLENOID VALVES

1/2" AND 3/4" OPTIONS UP TO 200 PSI  
NSF/ANSI/CAN 61 AND NSF/ANSI/CAN 372 CERTIFICATION FOR DRINKING WATER

GC Valves' True Union series of solenoid valves offer a convenient and easy-to-service option for 1/2" and 3/4" solenoid valve applications. Our True Union fittings streamline the installation process and make it simple to remove the valve for cleaning or maintenance.

The compact nature of the True Union fittings is also advantageous for OEMs looking to streamline product designs and simplify repair procedures. We have added wrench flats to the fittings to accommodate locations with limited clearance for tools.

GC Valves' NSF 61 and NSF 372 True Union valves are perfect for drinking water applications that require lead-free materials and compliance with federal drinking water regulations. Reach out to your local GC Valves sales manager or distributor for additional information!



## Features

- Allows for compact piping arrangements
- Easy removal for cleaning and servicing in the field
- Wrench flats on fittings help protect valve from damage during install/removal
- NSF approved options
- UL recognized, CSA, and CE options
- Great for OEMs looking to reduce plumbing complexity and footprint


## Applications

- Water treatment (ozone, UV, reverse osmosis, sterilizers)
- Drinking water applications
- Car Wash
- Food and Beverage (bottling, craft beverages, produce mister, cleaning)
- Clean-in-Place (CIP) applications
- Commercial buildings, Hospitals, Medical facilities
- Agricultural Applications

# TRUE UNION SPECS WITH PART NUMBERS

Pipe Size (NPT)	Orifice Size (in)	Flow Factor (Cv)	Operating Pressure Differential (PSI)					Part Number		Power Consumption		NSF-61-G NSF-372
			Min.	Max. (Air/ Gas)		Max. (Water)		DIN Coil*	Lead Wire Coil*			
				AC	DC	AC	DC			AC	DC	
Normally Closed - EPDM Seals												
1/2"	3/4	4.3	0	140	90	140	90	T201YF02CPD2	T201GF02CPD2	10W	10W	No
	3/4	4.3	4	200	150	150	100	T211YF02CPD2	T211GF02CPD2	8W	10W	No
	3/4	4.3	5	150	80	150	80	TP31YN02CPD2	TP31GN02CPD2	6.5vA	8W	No
3/4"	3/4	6.7	0	140	90	140	90	T201YF02CPE2	T201GF02CPE2	10W	10W	No
	3/4	6.7	4	200	150	150	100	T211YF02CPE2	T211GF02CPE2	8W	10W	No
	3/4	6.7	5	150	80	150	80	TP31YN02CPE2	TP31GN02CPE2	6.5vA	8W	No
Normally Open - EPDM Seals												
1/2"	3/4	4.3	0	200	125	200	125	T202YF02CPD2	T202GF02CPD2	11W	10W	No
	3/4	4.3	4	200	140	200	125	T212YF02CPD2	T212GF02CPD2	11W	10W	No
3/4"	3/4	6.7	0	200	125	200	125	T202YF02CPE2	T202GF02CPE2	11W	10W	No
	3/4	6.7	4	200	140	150	140	T212YF02CPE2	T212GF02CPE2	11W	10W	No
NSF - Normally Closed - EPDM Seals												
1/2"	3/4	4.3	0	140	90	140	90	NT201YF02CPD2	NT201GF02CPD2	10W	10W	Yes
	3/4	4.3	4	200	150	150	100	NT211YF02CPD2	NT211GF02CPD2	8W	10W	Yes
	3/4	4.3	5	150	80	150	80	NTP31YN02CPD2	NTP31GN02CPD2	6.5vA	8W	Yes
3/4"	3/4	6.7	0	140	90	140	90	NT201YF02CPE2	NT201GF02CPE2	10W	10W	Yes
	3/4	6.7	4	200	150	150	100	NT211YF02CPE2	NT211GF02CPE2	8W	10W	Yes
	3/4	6.7	5	150	80	150	80	NTP31YN02CPE2	NTP31GN02CPE2	6.5vA	8W	Yes
NSF - Normally Open - EPDM Seals												
1/2"	3/4	4.3	0	200	125	200	125	NT202YF02CPD2	NT202GF02CPD2	11W	10W	Yes
	3/4	4.3	4	200	140	200	125	NT212YF02CPD2	NT212GF02CPD2	11W	10W	Yes
3/4"	3/4	6.7	0	200	125	200	125	NT202YF02CPE2	NT202GF02CPE2	11W	10W	Yes
	3/4	6.7	4	200	140	150	140	NT212YF02CPE2	NT212GF02CPE2	11W	10W	Yes

\* 120 vAC part numbers shown, more voltage options available



456 Crompton Street  
Charlotte, NC 28273  
Tel: 800-828-0484

gcv valves.com  
sales@gcvalves.com